## NSN 5950-01-212-7146

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-212-7146

Thread Class (non-core):
Unable to decode
Thread Direction (non-core):
Unable to decode
Reliability Indicator:
Not established
Overall Length:
5.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.250 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.250 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Width:
4.000 inches
Body Height:
2.188 inches
Inclosure Type:
Fully enclosed
Tully eliclosed
Mounting Facility Quantity:
Mounting Facility Quantity:
Mounting Facility Quantity: 4 single group
Mounting Facility Quantity: 4 single group Mounting Method:
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group  Winding Function And Quantity:
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group  Winding Function And Quantity: 1 primary and 3 secondary single component
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group  Winding Function And Quantity: 1 primary and 3 secondary single component  Thready Qty Per Inch (tpi):
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group  Winding Function And Quantity: 1 primary and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group  Winding Function And Quantity: 1 primary and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Thread Size:
Mounting Facility Quantity: 4 single group Mounting Method: Bracket and threaded hole single group Winding Function And Quantity: 1 primary and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group  Winding Function And Quantity: 1 primary and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.190 inches single group  Winding Operating Current:
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group  Winding Function And Quantity: 1 primary and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.190 inches single group  Winding Operating Current: 2.0 amperes dc single component 2nd secondary
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group  Winding Function And Quantity: 1 primary and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.190 inches single group  Winding Operating Current: 2.0 amperes dc single component 2nd secondary  Winding Operating Voltage:
Mounting Facility Quantity: 4 single group  Mounting Method: Bracket and threaded hole single group  Winding Function And Quantity: 1 primary and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.190 inches single group  Winding Operating Current: 2.0 amperes dc single component 2nd secondary  Winding Operating Voltage: 88.00 dc volts single component 3rd secondary
Mounting Facility Quantity:  4 single group  Mounting Method:  Bracket and threaded hole single group  Winding Function And Quantity:  1 primary and 3 secondary single component  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.190 inches single group  Winding Operating Current:  2.0 amperes dc single component 2nd secondary  Winding Operating Voltage:  88.00 dc volts single component 3rd secondary  Thread Series Designator:
Mounting Facility Quantity:  4 single group  Mounting Method:  Bracket and threaded hole single group  Winding Function And Quantity:  1 primary and 3 secondary single component  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.190 inches single group  Winding Operating Current:  2.0 amperes dc single component 2nd secondary  Winding Operating Voltage:  88.00 dc volts single component 3rd secondary  Thread Series Designator:  Unf single group

N/a

## NSN 5950-01-212-7146

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0