NSN 5950-01-213-1916

Power Transformer - Page 1 of 2

Thread Class (non-core):

Thread Direction (non-core):

Unable to decode

Unable to decode



View Online at https://aerobasegroup.com/nsn/5950-01-213-1916

Reliability Indicator: Not established **Center To Center Distance Between Mounting Facilities Parallel To Length:** 3.350 inches single mounting facility single center group **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.500 inches single mounting facility single center group Frequency Rating: 380.0 hertz and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component **Body Length:** 4.250 inches **Body Width:** 2.850 inches **Body Height:** 2.950 inches **Maximum Operating Temp:** 85.0 degrees celsius **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded hole single group **Winding Function And Quantity:** 1 primary and 3 secondary single component **Thread Size:** 0.190 inches single group **Winding Operating Current:** 8.0 amperes ac single component 1st secondary **Winding Operating Voltage:** 55.54 ac volts single component 3rd secondary **Thread Series Designator:** Unf single group **Terminal Type And Quantity:** 9 tab, solder lug Shelf Life: N/a

NSN 5950-01-213-1916

Power Transformer - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A058b0