NSN 5950-01-213-1916

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-213-1916

| Thread Class (non-core): |
|---|
| Unable to decode |
| Thread Direction (non-core): |
| Unable to decode |
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.350 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.500 inches single mounting facility single center group |
| Frequency Rating: |
| 380.0 hertz and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 4.250 inches |
| Body Width: |
| 2.850 inches |
| Body Height: |
| 2.950 inches |
| Maximum Operating Temp: |
| 85.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary and 3 secondary single component |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 8.0 amperes ac single component 1st secondary |
| Winding Operating Voltage: |
| 55.54 ac volts single component 3rd secondary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 9 tab, solder lug |
| Shelf Life: |
| N/a |

NSN 5950-01-213-1916

Power Transformer - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0

