NSN 5950-01-214-0981

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-214-0981

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and fungus resistant

Overall Length:

4.050 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.677 inches and 3.697 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.302 inches and 1.322 inches single mounting facility single center group

Overall Height:

2.826 inches

Overall Width:

1.880 inches

Mounting Hole Diameter:

0.200 inches and 0.206 inches single group

Frequency Rating:

20.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Cubic Measure (non-core):

21.51 cubic inches

Winding Operating Current:

98.9 amperes ac single component single secondary

Winding Power Rating:

1.609 kilovolt-amperes single component single secondary

Winding Operating Voltage:

16.26 ac volts single component single secondary

Terminal Type And Quantity:

3 tab, solder lug and 4 turret

Shelf Life:

N/a

NSN 5950-01-214-0981

Power Transformer - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A058b0