

View Online at <https://aerobasegroup.com/nsn/5950-01-214-5717>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches single mounting facility single center group

Mounting Hole Diameter:

0.186 inches single group and 0.196 inches single group

Frequency Rating:

10.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal 2nd component

Body Length:

Between 2.075 inches and 2.105 inches

Body Width:

Between 1.515 inches and 1.545 inches

Body Height:

1.940 inches

Maximum Operating Temp:

71.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Cubic Measure (non-core):

6.3 cubic inches

Winding Operating Current:

240.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

75.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0