NSN 5950-01-215-2168

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-215-2168 Thread Class (non-core): Unable to decode Thread Direction (non-core): Unable to decode **Reliability Indicator:** Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 3.120 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.880 inches single mounting facility single center group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component **Transformer Winding Connection Type:** Delta-delta **Maximum Transformer Power Rating:** 70.0 watts single component **Winding Shielding Method:** Internal shield grounded to core and brought out to terminal single component **Body Length:** 3.750 inches **Body Width:** 2.750 inches **Body Height:** 2.000 inches **Maximum Operating Temp:** 70.0 degrees celsius **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded hole single group **Winding Function And Quantity:** 1 primary and 1 secondary single component Cubic Measure (non-core): 20.63 cubic inches **Thread Size:**

0.164 inches single group

Winding Operating Current:

250.0 milliamperes ac single component single primary

NSN 5950-01-215-2168

Power Transformer - Page 2 of 2



windin	g Opera	ating v	oitage:
445.00		مام مام	

115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0