Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-215-4711 |
|---|
| Thread Class (non-core): |
| Unable to decode |
| Thread Direction (non-core): |
| Unable to decode |
| Reliability Indicator: |
| Not established |
| Frequency Rating: |
| 380.0 hertz and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 0.375 inches |
| Body Outside Diameter: |
| 1.062 inches |
| Maximum Operating Temp: |
| 155.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 1 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary and 1 secondary single component |
| Thread Size: |
| 0.112 inches single group |
| Winding Operating Current: |
| 40.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 25.22 ac volts $% \left(22,22,22,22,22,22,22,22,22,22,22,22,22,$ |
| Unpackaged Unit Weight (non-core): |
| 0.080 pounds |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 5 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| N I - |

No

NSN 5950-01-215-4711

Power Transformer - Page 2 of 2

Fiig: A058b0

