NSN 5950-01-215-7234

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-215-7234

Dummy Terminal Quantity (non-core):
6
Reliability Indicator:
Not established
Overall Length:
0.820 inches
Overall Height:
0.420 inches
Overall Width:
0.620 inches
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Maximum Operating Temp:
130.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Method:
Mounting Method: Terminal single group
-
Terminal single group
Terminal single group Winding Function And Quantity:
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core):
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches Winding Operating Voltage:
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches Winding Operating Voltage: 26.00 ac volts single component single secondary
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches Winding Operating Voltage: 26.00 ac volts single component single secondary Terminal Type And Quantity:
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches Winding Operating Voltage: 26.00 ac volts single component single secondary Terminal Type And Quantity: 4 pin
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches Winding Operating Voltage: 26.00 ac volts single component single secondary Terminal Type And Quantity: 4 pin Shelf Life:
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches Winding Operating Voltage: 26.00 ac volts single component single secondary Terminal Type And Quantity: 4 pin Shelf Life: N/a
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches Winding Operating Voltage: 26.00 ac volts single component single secondary Terminal Type And Quantity: 4 pin Shelf Life: N/a Unit Of Measure:
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches Winding Operating Voltage: 26.00 ac volts single component single secondary Terminal Type And Quantity: 4 pin Shelf Life: N/a Unit Of Measure:
Terminal single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 0.213 cubic inches Winding Operating Voltage: 26.00 ac volts single component single secondary Terminal Type And Quantity: 4 pin Shelf Life: N/a Unit Of Measure: Demilitarization: