

View Online at <https://aerobasegroup.com/nsn/5950-01-216-1054>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

30.0 volt-ampere single component

Winding Shielding Method:

Internally shielded single component

Body Length:

3.130 inches

Body Width:

2.750 inches

Body Height:

2.750 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary and 3 secondary single component

Cubic Measure (non-core):

23.7 cubic inches

Winding Operating Current:

600.0 milliamperes ac single component 3rd secondary

Winding Power Rating:

9.9 volts-amperes single component 1st secondary

Winding Operating Voltage:

36.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0