

View Online at <https://aerobasegroup.com/nsn/5950-01-216-3636>

Reliability Indicator:

Not established

Overall Length:

78.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Length:

71.0 millimeters single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

60.0 millimeters single mounting facility single center group

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

48.3 volt-ampere single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Width:

48.0 millimeters

Body Height:

68.0 millimeters

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket and slot single group

Cooling Method:

Self-cooled

Winding Function And Quantity:

2 primary and 5 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

700.0 milliamperes dc single component 3rd secondary

Winding Operating Voltage:

90.00 ac volts single component 4th secondary

Special Features:

Two primary windings; five secondary windings, with third through fifth windings center tapped

Terminal Type And Quantity:

3 connector, receptacle and 6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0