

View Online at <https://aerobasegroup.com/nsn/5950-01-216-3639>

**Thread Class (non-core):**

Unable to decode

**Thread Direction (non-core):**

Unable to decode

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

13.750 inches 3rd mounting facili type 3rd center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

8.000 inches 3rd mounting facili type 3rd center group

**Mounting Hole Diameter:**

0.100 inches 2nd group

**Mounting Slot Width:**

0.568 inches 1st group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

15.250 inches

**Body Width:**

12.250 inches

**Body Height:**

14.000 inches

**Maximum Operating Temp:**

220.0 degrees celsius

**Distance Between Mounting Facility Centers:**

10.000 inches 2nd mounting facili type 2nd center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 3rd group

**Mounting Method:**

Unthreaded hole 2nd group

**Winding Function And Quantity:**

1 primary and 1 secondary single component

**Cubic Measure (non-core):**

2615.4 cubic inches

**Thread Size:**

0.500 inches 3rd group

**Winding Operating Current:**

20.0 amperes ac single component single secondary

**Winding Power Rating:**

17.26 kilovolt-amperes single component single secondary

**Winding Operating Voltage:**

863.00 ac volts single component single secondary

**Thread Series Designator:**

Unc 3rd group

**Terminal Type And Quantity:**

4 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0