

View Online at <https://aerobasegroup.com/nsn/5950-01-216-3639>

Thread Class (non-core):

Unable to decode

Thread Direction (non-core):

Unable to decode

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

13.750 inches 3rd mounting facili type 3rd center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

8.000 inches 3rd mounting facili type 3rd center group

Mounting Hole Diameter:

0.100 inches 2nd group

Mounting Slot Width:

0.568 inches 1st group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

15.250 inches

Body Width:

12.250 inches

Body Height:

14.000 inches

Maximum Operating Temp:

220.0 degrees celsius

Distance Between Mounting Facility Centers:

10.000 inches 2nd mounting facili type 2nd center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 3rd group

Mounting Method:

Unthreaded hole 2nd group

Winding Function And Quantity:

1 primary and 1 secondary single component

Cubic Measure (non-core):

2615.4 cubic inches

Thread Size:

0.500 inches 3rd group

Winding Operating Current:

20.0 amperes ac single component single secondary

Winding Power Rating:

17.26 kilovolt-amperes single component single secondary

Winding Operating Voltage:

863.00 ac volts single component single secondary

Thread Series Designator:

Unc 3rd group

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0