# NSN 5950-01-216-7293

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-216-7293

# Center To Center Distance Between Mounting Facilities Parallel To Length:

4.812 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

4.812 inches single mounting facility single center group

## Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Body Length:**

5.531 inches

**Body Width:** 

5.531 inches

Body Height:

4.531 inches

#### Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

# Mounting Method:

Threaded stud single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

## Thready Qty Per Inch (tpi):

32 single group

#### Thread Size:

0.190 inches single group

## **Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unf single group

#### **Terminal Type And Quantity:**

7 tab, solder lug

**Specification Data:** 

81349-mil-t-27/235 government specification

# Shelf Life:

N/a

Unit Of Measure:

- --
- Demilitarization:

No

# NSN 5950-01-216-7293

Power Transformer - Page 2 of 2

**Fiig:** A058b0

