

View Online at <https://aerobasegroup.com/nsn/5950-01-217-2322>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.875 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.375 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

125.0 volt-ampere single component

**Body Length:**

2.250 inches

**Body Width:**

1.750 inches

**Body Height:**

1.656 inches

**Maximum Operating Temp:**

170.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

22.5 amperes ac single component 2nd secondary

**Winding Operating Voltage:**

5.57 ac volts single component 2nd secondary

**Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 tab, solder lug

**Specification Data:**

81349-mil-t-27/223 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0