NSN 5950-01-217-4091



Power Transformer - Page 1 of 2	Grou
View Online at https://aerobasegroup.com/nsn/5950-01-217-4091	
Thread Class (non-core):	
Unable to decode	
Thread Direction (non-core):	
Unable to decode	
Reliability Indicator:	
Not established	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
3.312 inches single mounting facility single center group	
Center To Center Distance Between Mounting Facilities Parallel To Width:	
2.687 inches single mounting facility single center group	
Frequency Rating:	
400.0 hertz single component	
Input-output Phase Relationship:	
Single phase to single phase single component	
Winding Shielding Method:	
Core grounded single component	
Body Length:	
3.875 inches	
Body Width:	
3.250 inches	
Body Height:	
2.680 inches	
Maximum Operating Temp:	
90.0 degrees celsius	
Inclosure Type:	
Fully enclosed	
Mounting Facility Quantity:	
4 single group	
Mounting Method:	
Threaded hole single group	
Winding Function And Quantity:	
1 primary and 5 secondary single component	

Cubic Measure (non-core):

2.6 cubic inches

Thread Size:

0.190 inches single group

Winding Operating Current:

6.0 amperes dc single component 1st secondary

Winding Operating Voltage:

31.60 ac volts single component 1st secondary

Special Features:

1 primary and 5 secondary windings; fifth secondary is center taped with 16.70 volts and 3 amps of current which has been rectified

NSN 5950-01-217-4091

Power Transformer - Page 2 of 2



T	'nr	ead	Series	Design	nator:

Unc single group

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0