NSN 5950-01-219-3048

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-219-3048

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group Mounting Hole Diameter: 0.218 inches single group **Frequency Rating:** 47.0 hertz and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component **Maximum Transformer Power Rating:** 300.0 volt-ampere single component Winding Shielding Method: Internal shield grounded to core single component **Body Length:** 4.560 inches **Body Width:** 3.810 inches **Body Height:** 4.130 inches **End Application:** Terminal, communications an/ugc-137av2 **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Unthreaded hole single group Winding Function And Quantity: 2 primary and 1 secondary single component Winding Operating Current: 10.0 amperes dc single component single secondary Winding Operating Voltage: 26.00 dc volts single component single secondary **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a Unit Of Measure:

--

NSN 5950-01-219-3048

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

