

View Online at <https://aerobasegroup.com/nsn/5950-01-219-6452>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Body Length:

5.500 inches

Body Width:

4.500 inches

Body Height:

6.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary and 7 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

750.0 milliamperes dc single component 3rd secondary

Winding Power Rating:

90.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

42.00 dc volts single component 4th secondary

Special Features:

One primary winding; seven secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

21 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0