

View Online at <https://aerobasegroup.com/nsn/5950-01-221-8029>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and internal shield grounded to secondary center tap single component

Body Length:

6.000 inches

Body Width:

3.125 inches

Body Height:

4.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

2 primary and 1 secondary single component

Cubic Measure (non-core):

84.4 cubic inches

Winding Operating Current:

8.1 amperes dc single component single secondary

Winding Power Rating:

711.2 volts-amperes single component single secondary

Winding Operating Voltage:

87.80 ac volts single component single secondary

Terminal Type And Quantity:

1 terminal block w/screws and 2 wire lead and 1 wire lead w/lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0