

View Online at <https://aerobasegroup.com/nsn/5950-01-222-0497>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.485 inches and 1.515 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.235 inches and 1.265 inches single mounting facility single center group

Mounting Hole Diameter:

0.171 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.940 inches

Body Width:

Between 1.610 inches and 1.650 inches

Body Height:

Between 1.670 inches and 1.710 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Winding Operating Current:

4.0 amperes ac single component single secondary

Winding Operating Voltage:

36.80 ac volts single component single secondary

Unpackaged Unit Weight (non-core):

10.000 ounces

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0