NSN 5950-01-222-0807

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-222-0807

Thread Class (non-core):

Unable to decode

Thread Direction (non-core):

Unable to decode

Reliability Indicator:

Not established

Overall Length:

Between 2.910 inches and 2.970 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.485 inches and 2.515 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.110 inches and 1.140 inches single mounting facility single center group

Overall Height:

1.850 inches

Overall Width:

Between 2.270 inches and 2.330 inches

Frequency Rating:

1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary and 3 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

3.5 amperes ac single component single primary

Winding Power Rating:

7.0 volts-amperes single component single primary

Winding Operating Voltage:

462.00 ac millivolts single component 2nd secondary

Special Features:

First secondary center tap split into two terminals

NSN 5950-01-222-0807

Power Transformer - Page 2 of 2



Inread Series Designator:
Unc single group
Terminal Type And Quantity:
13 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0