

View Online at <https://aerobasegroup.com/nsn/5950-01-222-4442>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

15.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.000 inches

Body Width:

1.780 inches

Body Height:

3.280 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

3 primary and 5 secondary single component

Cubic Measure (non-core):

17.5 cubic inches

Winding Operating Current:

6.0 amperes dc single component 2nd secondary

Winding Operating Voltage:

8.48 ac volts single component 2nd primary

Special Features:

All secondary outputs are displayed as rectified voltages; 2nd secondary provides a negative voltage output; secondaries 3, 4, 5 provide pos and neg voltage outputs; 5th secondary outputs are pos 57.00 or neg 57.00 v dc w/ 0.5 amps min and 1.0 amps max; 3 primary windings and 5 secondary windings

Unpackaged Unit Weight (non-core):

1.600 pounds

Terminal Type And Quantity:

24 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0