

View Online at <https://aerobasegroup.com/nsn/5950-01-222-4445>

Thread Class (non-core):

Unable to decode

Thread Direction (non-core):

Unable to decode

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.250 inches single mounting facility single center group

Frequency Rating:

380.0 hertz and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal single component

Body Length:

6.250 inches

Body Width:

Between 4.140 inches and 4.260 inches

Body Height:

5.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary and 4 secondary single component

Cubic Measure (non-core):

153.1 cubic inches

Thread Size:

0.250 inches single group

Winding Operating Current:

250.0 milliamperes dc single component 4th secondary

Winding Operating Voltage:

50.86 ac volts and 52.94 ac volts single component 1st secondary

Special Features:

5 internal shields exit to 5 terminals; all output currents are stated as rectified

Unpackaged Unit Weight (non-core):

20.000 pounds

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

36 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A058b0