

View Online at <https://aerobasegroup.com/nsn/5950-01-223-0005>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Flame resistant and fungus resistant and moisture resistant and salt spray resistant and vibration resistant

Overall Length:

2.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.813 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Overall Height:

1.400 inches

Overall Width:

2.260 inches

Mounting Hole Diameter:

0.154 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase and three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Maximum Transformer Power Rating:

9.0 watts single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange and unthreaded hole single group

Winding Function And Quantity:

1 primary and 5 secondary single component

Features Provided:

Tinned wire leads

Cubic Measure (non-core):

8.7 cubic inches

Inclosure Material (non-core):

Plastic polytetrafluoroethylene

Winding Operating Current:

7.0 amperes ac single component 4th secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Special Features:

1 primary winding; 5 secondary windings

Unpackaged Unit Weight (non-core):

1.300 pounds

Terminal Type And Quantity:

17 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0