

View Online at <https://aerobasegroup.com/nsn/5950-01-223-0005>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Flame resistant and fungus resistant and moisture resistant and salt spray resistant and vibration resistant

**Overall Length:**

2.750 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.813 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.750 inches single mounting facility single center group

**Overall Height:**

1.400 inches

**Overall Width:**

2.260 inches

**Mounting Hole Diameter:**

0.154 inches single group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to single phase and three phase to three phase single component

**Transformer Winding Connection Type:**

Wye-delta

**Maximum Transformer Power Rating:**

9.0 watts single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange and unthreaded hole single group

**Winding Function And Quantity:**

1 primary and 5 secondary single component

**Features Provided:**

Tinned wire leads

**Cubic Measure (non-core):**

8.7 cubic inches

**Inclosure Material (non-core):**

Plastic polytetrafluoroethylene

**Winding Operating Current:**

7.0 amperes ac single component 4th secondary

**Winding Operating Voltage:**

115.00 ac volts single component single primary

**Special Features:**

1 primary winding; 5 secondary windings

**Unpackaged Unit Weight (non-core):**

1.300 pounds

**Terminal Type And Quantity:**

17 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A058b0