

View Online at <https://aerobasegroup.com/nsn/5950-01-223-1124>

**Thread Class (non-core):**

Unable to decode

**Thread Direction (non-core):**

Unable to decode

**Reliability Indicator:**

Not established

**Overall Length:**

5.700 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.880 inches and 4.920 inches single mounting facility type 2nd center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.180 inches and 3.220 inches single mounting facility single center group

**Overall Height:**

4.020 inches

**Overall Width:**

4.775 inches

**Frequency Rating:**

380.0 hertz and 420.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Transformer Winding Connection Type:**

Wye-wye

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

5.700 inches

**Body Width:**

4.775 inches

**Body Height:**

4.020 inches

**Maximum Operating Temp:**

180.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

8 single group

**Mounting Method:**

Flange and threaded hole single group

**Winding Function And Quantity:**

1 primary and 1 secondary single component

**Cubic Measure (non-core):**

109.4 cubic inches

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

123.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

4825.00 ac volts and 5025.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0