

View Online at <https://aerobasegroup.com/nsn/5950-01-223-1125>

**Thread Class (non-core):**

Unable to decode

**Thread Direction (non-core):**

Unable to decode

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.600 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.100 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

53.2 volt-ampere single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

2.100 inches

**Body Width:**

1.650 inches

**Body Height:**

1.820 inches

**Maximum Operating Temp:**

155.0 degrees celsius

**Inclosure Type:**

Partially enclosed, half shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary and 2 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

8.3 amperes ac single component 1st secondary

**Winding Power Rating:**

52.5 volts-amperes single component 1st secondary

**Winding Operating Voltage:**

6.32 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0