NSN 5950-01-223-1126

Power Transformer - Page 1 of 2

8.00 ac volts single component 4th secondary



View Online at https://aerobasegroup.com/nsn/5950-01-223-1126

Thread Class (non-core):
Unable to decode
Thread Direction (non-core):
Unable to decode
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.200 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.960 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Transformer Winding Connection Type:
Wye-delta
Maximum Transformer Power Rating:
280.8 volt-ampere single component
Body Length:
3.400 inches
Body Width:
3.150 inches
Body Height:
1.870 inches
Maximum Operating Temp:
180.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary and 4 secondary single component
Thread Size:
0.138 inches single group
Winding Operating Current:
820.0 milliamperes ac single component 1st secondary
Winding Power Rating:
49.0 volts-amperes single component 3rd secondary
Winding Operating Voltage:

NSN 5950-01-223-1126

Power Transformer - Page 2 of 2



Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0