# NSN 5950-01-223-3657



| Power Transformer - Page 1 of 2   |
|---|
| View Online at https://aerobasegroup.com/nsn/5950-01-223-3657             |
| Reliability Indicator:  |
| Not established   |
| Overall Length:   |
| 3.125 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.500 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.375 inches single mounting facility single center group                 |
| Overall Height:   |
| 3.812 inches  |
| Overall Width:  |
| 2.750 inches  |
| Mounting Slot Width:  |
| 0.188 inches single group   |
| Frequency Rating:   |
| 50.0 hertz or 60.0 hertz single component                                 |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to core single component                         |
| End Application:  |
| Test facility, electronic equipment oq-29 (v) 2/msm                       |
| Inclosure Type:   |

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Slot single group

#### **Winding Function And Quantity:**

1 primary and 1 secondary single component

#### **Cubic Measure (non-core):**

32.7 cubic inches

# **Winding Operating Current:**

8.0 amperes ac single component single secondary

#### Winding Power Rating:

60.0 volts-amperes single component single secondary

#### **Winding Operating Voltage:**

7.50 ac volts single component single secondary

# **Unpackaged Unit Weight (non-core):**

4.700 pounds

#### **Terminal Type And Quantity:**

5 wire lead

# NSN 5950-01-223-3657

Power Transformer - Page 2 of 2



| _ |    |      |   |        |  |
|---|----|------|---|--------|--|
| c | hο | JIF. |   | .ife:  |  |
| J |    |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0