

View Online at <https://aerobasegroup.com/nsn/5950-01-223-6346>

Thread Class (non-core):

Unable to decode

Thread Direction (non-core):

Unable to decode

Reliability Indicator:

Not established

Overall Length:

Between 4.031 inches and 4.093 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.984 inches and 3.016 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.609 inches and 2.641 inches single mounting facility single center group

Overall Height:

Between 5.501 inches and 5.687 inches

Overall Width:

Between 3.344 inches and 3.406 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

200.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Cubic Measure (non-core):

72.0 cubic inches

Thread Size:

0.250 inches single group

Winding Operating Current:

8.0 amperes ac single component single secondary

Winding Operating Voltage:

25.00 ac volts single component single secondary

Unpackaged Unit Weight (non-core):

10.500 pounds

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A058b0