NSN 5950-01-223-9395

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-223-9395

| Thread Class (non acro) |
|---|
| Thread Class (non-core): Unable to decode |
| Thread Direction (non-core): |
| Unable to decode |
| |
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.130 inches and 2.150 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.030 inches and 2.070 inches single mounting facility single center group |
| Overall Height: |
| 1.670 inches |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to single phase and three phase to three phase single component |
| Transformer Winding Connection Type: |
| Wye-delta |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |
| 3.320 inches |
| Body Width: |
| 2.760 inches |
| Maximum Operating Temp: |
| 155.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary and 4 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 60.0 milliamperes dc single component 4th secondary |
| Winding Power Rating: |
| 70.0 volts-amperes single component 2nd secondary |
| Winding Operating Voltage: |
| 8.50 dc volts single component 3rd secondary |
| |

NSN 5950-01-223-9395

Power Transformer - Page 2 of 2



Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0