NSN 5950-01-224-9512

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-224-9512

Thread Class (non-core): Unable to decode Thread Direction (non-core): Unable to decode **Reliability Indicator:** Not established **Overall Length:** Between 3.094 inches and 3.156 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.484 inches and 2.516 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.984 inches and 2.016 inches single mounting facility single center group **Overall Height:** Between 4.376 inches and 4.624 inches **Overall Width:** Between 2.594 inches and 2.656 inches **Frequency Rating:** 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component **Maximum Transformer Power Rating:** 80.0 volt-ampere single component Winding Shielding Method: Internal shield grounded to core single component Maximum Operating Temp: 105.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Cubic Measure (non-core): 31.9 cubic inches **Thread Size:** 0.164 inches single group Winding Operating Current: 3.64 amperes ac single component single secondary Winding Operating Voltage: 22.00 ac volts single component single secondary

NSN 5950-01-224-9512

Power Transformer - Page 2 of 2



Unpackaged Unit Weight (non-core):

5.000 pounds

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0