Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-225-6671

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.625 inches single mounting facility single center group |
| Impedance Rating In Ohms: |
| 30000.0 single component single secondary |
| Frequency Rating: |
| 3.5 kilohertz single component |
| Maximum Transformer Power Rating: |
| 5.0 milliwatts single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 1.270 inches |
| Body Width: |
| 1.020 inches |
| Body Height: |
| 1.140 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary and 1 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 0.5 milliamperes dc single component single secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5950-01-225-6671

Audio Frequency Transformer - Page 2 of 2

Fiig: A058b0

