

View Online at <https://aerobasegroup.com/nsn/5950-01-225-8755>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.088 inches and 3.152 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.747 inches and 2.872 inches single mounting facility single center group

Mounting Slot Width:

0.250 inches single group

Frequency Rating:

59.0 hertz and 61.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 3.750 inches and 3.875 inches

Body Width:

3.875 inches

Body Height:

4.625 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

3 primary and 5 secondary single component

Features Provided:

Color coded lead

Cubic Measure (non-core):

69.4 cubic inches

Winding Operating Current:

300.0 milliamperes ac single component all primary

Winding Operating Voltage:

5.00 dc volts single component 1st secondary

Special Features:

Three primary windings and five secondary windings

Terminal Type And Quantity:

19 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0