

View Online at <https://aerobasegroup.com/nsn/5950-01-225-8779>

Thread Class (non-core):

Unable to decode

Thread Direction (non-core):

Unable to decode

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.120 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

0.562 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Cubic Measure (non-core):

0.63 cubic inches

Thread Size:

0.138 inches single group

Winding Operating Current:

2.25 amperes ac single component single secondary

Winding Power Rating:

65.0 volts-amperes single component single primary

Winding Operating Voltage:

26.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0