NSN 5950-01-227-1522

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-227-1522

| Thread Class (non-core): |
|---|
| Unable to decode |
| Thread Direction (non-core): |
| Unable to decode |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 3.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.450 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.250 inches single mounting facility single center group |
| Overall Height: |
| 1.880 inches |
| Overall Width: |
| 2.250 inches |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary and 4 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 1.88 amperes ac single component 1st secondary |
| Winding Power Rating: |
| 190.0 volts-amperes single component single primary |
| Winding Operating Voltage: |
| 199.00 ac volts single component single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 15 tab, solder lug |
| Shelf Life: |
| N/a |

NSN 5950-01-227-1522

Power Transformer - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0

