NSN 5950-01-227-4560

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-227-4560

Thread Class (non-core):

Unable to decode

Thread Direction (non-core):

Unable to decode

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.990 inches and 4.010 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.930 inches and 2.950 inches single mounting facility single center group

Frequency Rating:

47.0 hertz and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

5.580 inches

Body Width:

3.700 inches

Body Height:

5.620 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

25.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

48.8 volts-amperes single component 2nd secondary

Winding Operating Voltage:

120.00 ac volts single component single primary

Thread Series Designator:

Unc single group

NSN 5950-01-227-4560

Power Transformer - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 6 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

Fiig:

A058b0