## NSN 5950-01-227-4560

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-227-4560

Thread Class (non-core):

Unable to decode

Thread Direction (non-core):

Unable to decode

**Reliability Indicator:** 

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.990 inches and 4.010 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

2.930 inches and 2.950 inches single mounting facility single center group

Frequency Rating:

47.0 hertz and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

**Winding Shielding Method:** 

Internal shield grounded to core single component

**Body Length:** 

5.580 inches

**Body Width:** 

3.700 inches

**Body Height:** 

5.620 inches

**Maximum Operating Temp:** 

130.0 degrees celsius

**Inclosure Type:** 

Fully enclosed

**Mounting Facility Quantity:** 

4 single group

**Mounting Method:** 

Threaded hole single group

Winding Function And Quantity:

1 primary and 2 secondary single component

**Thread Size:** 

0.164 inches single group

**Winding Operating Current:** 

25.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

48.8 volts-amperes single component 2nd secondary

**Winding Operating Voltage:** 

120.00 ac volts single component single primary

**Thread Series Designator:** 

Unc single group

## NSN 5950-01-227-4560

Power Transformer - Page 2 of 2



Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0