NSN 5950-01-227-9036

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-227-9036

| · |
|---|
| Thread Class (non-core): |
| Unable to decode |
| Thread Direction (non-core): |
| Unable to decode |
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 6.000 inches 1st mounting facili type 1st center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 9.250 inches 1st mounting facili type 1st center group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 8.000 inches |
| Body Width: |
| 10.500 inches |
| Body Height: |
| 10.000 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 6 1st group |
| Mounting Method: |
| Threaded stud 1st group |
| Winding Function And Quantity: |
| 1 primary and 1 secondary single component |
| Thread Size: |
| 0.375 inches 2nd group |
| Winding Operating Current: |
| 15.0 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 440.00 ac volts single component single primary |
| Thread Series Designator: |
| Unf 2nd group |
| Terminal Type And Quantity: |
| 2 tob colder lug and 2 turnet |
| 2 tab, solder lug and 2 turret |
| Shelf Life: |
| |

--

NSN 5950-01-227-9036

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0