NSN 5950-01-229-2676

Audio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-229-2676

| Reliability Indicator: |
|--|
| Not established |
| Hazardous Locations/environmental Protection: |
| Vibration resistant |
| Impedance Rating In Ohms: |
| 10000.0 single component single primary and 12000.0 single component single primary |
| Frequency Rating: |
| 300.0 hertz single component and 20.0 kilohertz single component |
| Maximum Transformer Power Rating: |
| 100.0 milliwatts single component |
| Body Length: |
| 0.562 inches |
| Overall Diameter: |
| 0.350 inches |
| Maximum Operating Temp: |
| 105.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Terminal single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 1.0 milliamperes dc single component single primary |
| Test Data Document: |
| 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 5 wire lead |
| Specification Data: |
| 81349-mil-t-27/76 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |