## NSN 5950-01-229-7273

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-229-7273

| Thread Class (non-core):  |  |  |  |  |  |  |
|---|--|--|--|--|--|--|
| Unable to decode  |  |  |  |  |  |  |
| Thread Direction (non-core):  |  |  |  |  |  |  |
| Unable to decode  |  |  |  |  |  |  |
| Reliability Indicator:  |  |  |  |  |  |  |
| Not established   |  |  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |  |  |  |  |  |  |
| 2.700 inches single mounting facility single center group                 |  |  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |  |  |  |  |  |  |
| 1.800 inches single mounting facility single center group                 |  |  |  |  |  |  |
| Frequency Rating:   |  |  |  |  |  |  |
| 380.0 hertz and 420.0 hertz single component                              |  |  |  |  |  |  |
| Input-output Phase Relationship:  |  |  |  |  |  |  |
| Three phase to three phase single component                               |  |  |  |  |  |  |
| Transformer Winding Connection Type:                                      |  |  |  |  |  |  |
| Wye-delta   |  |  |  |  |  |  |
| Body Length:  |  |  |  |  |  |  |
| 3.260 inches  |  |  |  |  |  |  |
| Body Width:   |  |  |  |  |  |  |
| 2.390 inches  |  |  |  |  |  |  |
| Body Height:  |  |  |  |  |  |  |
| 2.375 inches  |  |  |  |  |  |  |
| End Application:  |  |  |  |  |  |  |
| Control-monitor set, an/awb- (v)  |  |  |  |  |  |  |
| Inclosure Type:   |  |  |  |  |  |  |
| Fully enclosed  |  |  |  |  |  |  |
| Mounting Facility Quantity:   |  |  |  |  |  |  |
| 4 single group  |  |  |  |  |  |  |
| Mounting Method:  |  |  |  |  |  |  |
| Threaded hole single group  |  |  |  |  |  |  |
| Winding Function And Quantity:  |  |  |  |  |  |  |
| 1 primary and 2 secondary single component                                |  |  |  |  |  |  |
| Thread Size:  |  |  |  |  |  |  |
| 0.138 inches single group   |  |  |  |  |  |  |
| Winding Operating Current:  |  |  |  |  |  |  |
| 825.0 milliamperes ac single component 2nd secondary                      |  |  |  |  |  |  |
| Winding Operating Voltage:  |  |  |  |  |  |  |
| 32.10 ac volts and 33.60 ac volts single component 1st secondary          |  |  |  |  |  |  |
| Thread Series Designator:   |  |  |  |  |  |  |
| Unc single group  |  |  |  |  |  |  |
| Terminal Type And Quantity:   |  |  |  |  |  |  |

10 turret

## NSN 5950-01-229-7273

Power Transformer - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0