## NSN 5950-01-230-2953

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-230-2953

Reliability Indicator:
Not established
Turn Quantity:
2-1/4 single component single winding
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.160 inches single mounting facility single center group  Contar To Contar Distance Returned Mounting Excilities Parallel To Width:
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.160 inches single mounting facility single center group
Mounting Hole Diameter:
0.094 inches single group
Inductance Type:
Fixed
Inductance Rating:
0.07 microhenries single component single winding and 0.09 microhenries single component single winding
Frequency Rating:
36.0 megahertz single component
Body Length:
0.500 inches
Body Width:
0.260 inches
Body Height:
0.260 inches
Maximum Operating Temp:
85.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Winding Conductor Size:
0.02010 inches american wire gage single component single winding
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-230-2953

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0