

View Online at <https://aerobasegroup.com/nsn/5950-01-230-9622>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.164 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

2.2 watts single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.120 inches

Body Outside Diameter:

1.920 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary and 2 secondary single component

Winding Operating Current:

8.4 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

27.20 ac volts and 30.00 ac volts and 33.30 ac volts single component 1st secondary

Unpackaged Unit Weight (non-core):

200.0 grams

Test Data Document:

05869-732519 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0