

View Online at <https://aerobasegroup.com/nsn/5950-01-231-3225>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.990 inches and 5.010 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.990 inches and 4.010 inches single mounting facility all center groupings

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 5.850 inches and 5.910 inches

Body Width:

Between 4.880 inches and 5.000 inches

Body Height:

Between 4.380 inches and 4.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary and 6 secondary single component

Thread Size:

0.250 inches all groupings

Winding Operating Current:

200.0 milliamperes dc and 250.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

9.70 ac volts single component 4th secondary

Thread Series Designator:

Unf all groupings

Terminal Type And Quantity:

20 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0