

View Online at <https://aerobasegroup.com/nsn/5950-01-232-2842>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Slot Width:

0.190 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.500 inches

Body Width:

2.500 inches

Body Height:

3.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Winding Operating Current:

500.0 milliamperes ac single component single primary

Winding Power Rating:

52.0 volts-amperes single component single primary

Winding Operating Voltage:

52.00 ac volts single component single secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 banana plug

Specification Data:

81349-mil-t-27/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0