

View Online at <https://aerobasegroup.com/nsn/5950-01-233-0769>

Thread Class (non-core):

Unable to decode

Thread Direction (non-core):

Unable to decode

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.490 inches and 1.510 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.990 inches and 2.010 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Body Length:

3.400 inches

Body Width:

3.000 inches

Body Height:

2.200 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary and 3 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

2.5 amperes dc single component 2nd secondary

Winding Power Rating:

65.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

26.00 dc volts single component 2nd secondary

Unpackaged Unit Weight (non-core):

2.700 pounds

Test Data Document:

96214-2859278 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0