NSN 5950-01-233-1235

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-233-1235

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 3.750 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.500 inches single mounting facility single center group |
| Overall Height: |
| 4.500 inches |
| Overall Width: |
| 3.062 inches |
| Mounting Hole Diameter: |
| 0.196 inches single group |
| Frequency Rating: |
| 50.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Operating Temp: |
| 170.0 degrees celsius |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary and 4 secondary single component |
| Cubic Measure (non-core): |
| 51.7 cubic inches |
| Winding Operating Current: |
| 3.0 amperes ac single component 3rd secondary |
| Winding Operating Voltage: |
| 9.00 ac volts single component 3rd secondary |
| Terminal Type And Quantity: |
| 10 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5950-01-233-1235

Power Transformer - Page 2 of 2



Fiig:

A058b0