# NSN 5950-01-233-1238

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-233-1238

Thread Class (non-core):

Unable to decode

Thread Direction (non-core):

Unable to decode

## **Reliability Indicator:**

Not established

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### Maximum Transformer Power Rating:

122.8 volt-ampere single component

#### Winding Shielding Method:

Internal shield brought out to terminal single component

**Body Length:** 

#### 1.100 inches

Body Outside Diameter:

3.050 inches

Inclosure Type:

Fully enclosed

**Mounting Facility Quantity:** 

1 single group

#### **Mounting Method:**

Threaded hole single group

#### Winding Function And Quantity:

1 primary and 6 secondary single component

## **Features Provided:**

Color coded lead

## Thread Size:

0.164 inches single group

#### Winding Operating Current:

720.0 milliamperes ac single component 1st secondary

#### Winding Operating Voltage:

9.60 ac volts and 28.00 ac volts and 37.60 ac volts single component 3rd secondary

#### **Special Features:**

One primary and six secondaries, fifth secondary center tapped and sixth secondary tapped w/o center

## **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

23 wire lead

## Shelf Life:

N/a

# NSN 5950-01-233-1238

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

