

View Online at <https://aerobasegroup.com/nsn/5950-01-233-3288>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Overall Length:

9.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.297 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Overall Height:

7.300 inches

Overall Width:

5.500 inches

Mounting Slot Width:

0.300 inches single group

Frequency Rating:

47.0 hertz and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

80.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary and 5 secondary single component

Cubic Measure (non-core):

393.47 cubic inches

Winding Operating Current:

3.9 amperes ac single component 3rd secondary

Winding Operating Voltage:

51.10 ac volts single component 1st secondary

Special Features:

2 primary windings; 5 secondary windings

Terminal Type And Quantity:

18 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0