

View Online at <https://aerobasegroup.com/nsn/5950-01-233-3288>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Humidity resistant and vibration resistant

**Overall Length:**

9.800 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

8.297 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.750 inches single mounting facility single center group

**Overall Height:**

7.300 inches

**Overall Width:**

5.500 inches

**Mounting Slot Width:**

0.300 inches single group

**Frequency Rating:**

47.0 hertz and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Maximum Operating Temp:**

80.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

2 primary and 5 secondary single component

**Cubic Measure (non-core):**

393.47 cubic inches

**Winding Operating Current:**

3.9 amperes ac single component 3rd secondary

**Winding Operating Voltage:**

51.10 ac volts single component 1st secondary

**Special Features:**

2 primary windings; 5 secondary windings

**Terminal Type And Quantity:**

18 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0