

View Online at <https://aerobasegroup.com/nsn/5950-01-234-8278>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

55.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to terminal single component

Body Length:

5.500 inches

Body Width:

4.750 inches

Body Height:

3.500 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

3.5 amperes ac single component 1st secondary

Winding Operating Voltage:

35.60 ac volts single component 1st secondary

Special Features:

1primary winding; 6secondary windings

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0